

We offer pressure reducing valves and overflow valves.

SCHLEY regulating valves are in use in many applications.



Our products for industrial applications

- Liquids
- Gases
- Steam

Pressure regulating valve T9

- DN15 bis DN200 (1/2" bis 8")
- PN16 – PN40
- outlet pressure: 0,5 – 20 bar
- for liquids and gases
- EN-JS1030, 1.0619, 1.4408, 1.4410, CC480K, CC333G



Pressure reducing valve T65

- DN15 bis DN200 (1/2" bis 8")
- PN16 – PN40
- outlet pressure: 1 – 40 bar
- for liquids and gases
- EN-JS1030, 1.0619, 1.4408, 1.4410, CC480K, CC333G



Pressure regulating valve T7

- DN15 bis DN200 (1/2" bis 8")
- PN16 – PN40
- outlet pressure: 0,5 – 20 bar
- for steam
- EN-JS1030, 1.0619, 1.7357, 1.4408



Pressure reducing valve T6

- DN15 bis DN200 (1/2" bis 8")
- PN16 – PN40
- outlet pressure: 1 – 40 bar
- for steam
- EN-JS1030, 1.0619, 1.7357, 1.4408



Pressure regulating valve T679

- DN15 bis DN65 (1/2" bis 2 1/2")
- PN16 – PN40
- outlet pressure: 0,5 – 20 bar
- with stainless steel bellow 1.4571
- for liquids, gases and steam
- EN-JS1030, 1.0619, 1.7357, 1.4408, 1.4410



Pressure reducing valve T95

- DN15 bis DN40 (1/2" bis 1 1/2")
- PN16 – PN40
- outlet pressure: 0,5 – 15 bar
- for liquids and gases
- CC480K, CC333G



Overflow valve T27F

- DN15 bis DN200 (1/2" bis 8")
- PN16 – PN40
- set pressure: 0,5 – 40 bar
- with stainless steel bellow 1.4571
- for liquids, gases and steam
- EN-JS1030, 1.0619, 1.4408, 1.4410, CC480K, CC333G



Overflow valve T27

- DN15 bis DN200 (1/2" bis 8")
- PN16 – PN40
- set pressure: 0,5 – 40 bar
- for liquids and gases
- EN-JS1030, 1.0619, 1.4408, 1.4410, CC480K, CC333G



Other pressures and pressure ratings on request.



Wilhelm Schley GmbH & Co. KG · Carl-Zeiss-Straße 4 · D-22946 Trittau

Tel. +49 - 4154 - 8081 - 0 · Fax +49 - 4154 - 8081 - 11 · www.wilhelm-schley.com

We offer pressure reducing valves or pressure regulating valves for the reduction of high pressure to lower pressure. SCHLEY pressure reducing valves are in use in many applications.



Our solutions for the oil and gas industry

- Power stations and thermal power stations
- Tank farms and storage tanks
- Shipbuilding and offshore facilities

Pressure regulating valve T9

Product features

- valve sizes DN15 (1/2") to DN200 (8")
- pressure rating PN16 - PN40, CL150 - CL300, 10K - 30K
other pressure ratings available on request
- flange according to DIN, ASME, ANSI, JIS
- materials EN-JS1030, 1.0619+N / WCB, 1.4408 / CF8M, 1.4410 / Super Duplex, CC480K / Bronze, CC333G / Aluminium bronze
- temperature range from -45°C to +200°C
- modular construction system (same construction parts for gas and liquids)
- with inside pulse line
- outlet pressure from 0,5 to 20 bar, lower or higher pressures available on request
- cone metallic sealing or with soft sealing
- suitable for compressible and incompressible media
- max. reduction ratio 25:1



Customer benefit

- compact construction type
- easy fit to the respective use because of the big variety of options
- same construction parts for gas, liquids and steam for an easier maintenance and repair
- inside spring (protected by bonnet)
- pulse line built at the valve, an installation of an external line is not necessary
- simple and robust construction type for a high reliability and easy maintenance
- seat ring is screwed in (DN15 to DN40)
- lower total operational cost due to the optimised construction
- safe against pressure surges (O-Ring sealing)
- high control accuracy
- constant control of the outlet pressure irrespective of inlet pressure
- valve locks up securely due to low pressure increase

Pressure reducing valve T65

Product features

- valve sizes DN15 (1/2") to DN200 (8")
- pressure rating PN16 - PN40, CL150 - CL300, 10K - 30K
other pressure ratings available on request
- flange according to DIN, ASME, ANSI, JIS
- materials EN-JS1030, 1.0619+N / WCB, 1.4408 / CF8M, 1.4410 / Super Duplex, CC480K / Bronze, CC333G / Aluminium bronze
- temperature range from -45°C to +200°C
- modular construction system (same construction parts for gas and liquids)
- with inside pulse line
- outlet pressure from 1 to 40 bar, lower and higher pressures available on request
- cone metallic sealing or with soft sealing
- suitable for compressible and incompressible media
- max. reduction ratio 25:1



Customer benefit

- compact construction type
- cost-efficient simple pressure reducing valve
- easy fit to the respective use because of the big variety of options
- same construction parts for gas, liquids and steam for an easier maintenance and repair
- inside spring (protected by bonnet)
- simple and robust construction type for a high reliability and easy maintenance
- seat ring screwed in (DN15 to DN40)
- lower total operational cost due to the optimised construction
- safe against pressure surges (O-Ring sealing)
- high control accuracy



Wilhelm Schley GmbH & Co. KG · Carl-Zeiss-Straße 4 · D-22946 Trittau

Tel. +49 - 4154 - 8081 - 0 · Fax +49 - 4154 - 8081 - 11 · www.wilhelm-schley.com

We offer pressure reducing valves or pressure regulating valves for the reduction of high pressure to lower pressure. SCHLEY pressure reducing valves are in use in many applications.



Our solutions for the steam control

- Power stations and thermal power stations
- Food industry
- Shipbuilding and offshore facilities

Pressure regulating valve T7

Product features

- valve sizes DN15 (1/2") to DN200 (8")
- pressure rating PN16 - PN40, CL150 - CL300, 10K - 30K
other pressure ratings available on request
- flange according to DIN, ASME, ANSI, JIS
- materials EN-JS1030, 1.0619+N / WCB, 1.7357 / WC6, 1.4408 / CF8M
- temperature range from -45°C to +450°C
- modular construction system (same construction parts for gas and liquids)
- with inside pulse line
- outlet pressure from 0,5 to 20 bar, lower or higher pressures available on request
- cone metallic sealing or with soft sealing
- suitable for compressible and incompressible media
- max. reduction ratio 25:1



Customer benefit

- compact construction type
- easy fit to the respective use because of the big variety of options
- same construction parts for gas, liquids and steam for an easier maintenance and repair
- inside spring (protected by bonnet)
- pulse line built at the valve, an installation of an external line is not necessary
- simple and robust construction type for a high reliability and easy maintenance
- seat ring is screwed in (DN15 to DN40)
- lower total operational cost due to the optimised construction
- safe against pressure surges (O-Ring sealing)
- high control accuracy
- constant control of the outlet pressure irrespective of inlet pressure
- valve locks up securely due to low pressure increase

Pressure reducing valve T6

Product features

- Valve sizes DN15 (1/2") to DN200 (8")
- pressure rating PN16 - PN40, CL150 - CL300, 10K - 30K
other pressure ratings available on request
- flange according to DIN, ASME, ANSI, JIS
- materials EN-JS1030, 1.0619+N / WCB, 1.7357 / WC6, 1.4408 / CF8M
- temperature range from -45°C to +450°C
- modular construction system (same construction parts for gas and liquids)
- with inside pulse line
- outlet pressure from 1 to 40 bar, lower and higher pressures available on request
- cone metallic sealing or with soft sealing
- suitable for compressible and incompressible media
- max. reduction ratio 25:1



Customer benefit

- compact construction type
- cost-efficient simple pressure reducing valve
- easy fit to the respective use because of the big variety of options
- same construction parts for gas, liquids and steam for an easier maintenance and repair
- inside spring (protected by bonnet)
- simple and robust construction type for a high reliability and easy maintenance
- seat ring screwed in (DN15 to DN40)
- lower total operational cost due to the optimised construction
- safe against pressure surges (O-Ring sealing)
- high control accuracy

